## Type 165 MBG 8-10 Roof conductor holder

For both 8 and 10 mm round wire

Now with larger base for green (living) flat roofs

**NEW** 

Mounting of any round conductor of Rd 8 mm or Rd 10 mm

UV-stabilised and weatherresistant closed shape with base

Can be used on almost all roofing felt systems



**Building Connections** 

## Roof conductor holder, type 165 MBG 8-10







- Closed form with base
- With double conductor holder for RD8 or RD10
- Filling weight 1 kg (frost-resistant concrete)
- Sleeve made of polyethylene, black, bottom polypropylene, black, UV-stabilised und weather-resistant
- Base made of polyamide PA 6, black, UV-stabilised and weather-resistant
- Can be used on almost all roofing felt systems (bitumen, PVC)
- Types 165 MBG...FO: Packed in foil bag

Туре	Fit mm	Pack. pcs.	Weight kg/100 pcs.	Item No.
165 MBG-8-10	-	12	100,000	5218700
165 MBG-8-10 FO	-	12	100,000	5218704

PA/PE Polyamide/Polyethylene0

- Closed form with base
- With double conductor holder for RD8 or RD10
- Filling weight 1 kg (frost-resistant concrete)
- Sleeve made of polyethylene, light grey, bottom polypropylene, light grey, UV-stabilised und weather-resistant
- Base made of polyamide PA 6, light grey, UV-stabilised and weather-resistant
- Can be used on almost all roofing felt systems (bitumen, PVC)

Туре	Fit	Fit			Weight	Item No.
	mm			pcs.	kg/100 pcs.	
165 MBG-8-10 G	iR –	grau		12	100,000	5218708

PA/PE Polyamid/Polyethylen

- Closed form with base
- With double conductor holder for RD8 or RD10
- Filling weight 1 kg (frost-resistant concrete)
- Sleeve made of polyethylene, black, bottom polypropylene, black, UV-stabilised und weather-resistant

• With larger base part (Ø 200 mm) for better stability Type Fit mm	Pack. pcs.		ght 00 pcs.	Item No.
165 MBG-8-10 200 –		12	100,000	5218716

PA/PE Polyamid/Polyethylen

OBO Bettermann Holding GmbH & Co. KG P.O. Box 1120 58694 Menden GERMANY Customer Service Tel.: +49 23 73 89 - 17 00 Fax: +49 23 73 89 - 12 38 export@obo.de

www.obo-bettermann.com

